



short facts

Performance

Max.diameter hardwood (in cm) (in cm)	42
Max.diameter softwood (in cm) (in cm)	56
Output approx. (in srm)	150

Intake opening

Feeding width (in mm)	1000
Feeding height (in mm)	650

Grinding unit

Rotor diameter (in mm)	820
Number of blades (half / full equipment) (in cm)	10 (20)

Material outfeed

Blower outfeed	✓
Conveyor belt outfeed	-

Main drive

Diesel engine	Mercedes Benz OM 471 LA
Electric motor (in kW/PS)	- 360 / 490
Power requirement (in kW)	-

Carriage

Number of axles	-
Top speed (in km/h)	-

Weight (without crane)

Weight basic model (in kg)	13000
Permitted axle load (in kg)	-
Permitted support load (in kg)	-
Permitted total weight (in kg)	-

Measurements transport position

Length (in mm)	6310
Width (in mm)	2550
Height (in mm)	2700

Control system

easygreen	✓
DIP	✓
Sensotronic	✓
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	-
15-channel remote control	-
Z-Tronic	-

HEM 561 DQ



Application

- shrubs and standing timber up to approx. 560 mm diameter
- high-powered chipper with large deployment radius

Specifics

- problem-free setup on hook lift HGV
- lowest-possible deadweight and compact dimensions
- largest chipper with add-on motor on 3-axle HGV
- large screen area for best chipping quality
- machine rotating for flexible work on both sides

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de