



Short Facts

Performance

Output approx. (in srm)	
Green waste	170
Bark	220
Scrap wood	110
Household waste	-

Infeed

Feeding width (in mm)	1500
Feeding height (in mm)	820
Infeed conveyor length (in mm)	4000
Silo capacity (in m³)	6

Grinding unit

Rotor diameter (in mm)	1040
Number of hammers	38

Material outfeed via conveyor belt

Discharge height (in mm)	3200
--------------------------	------

Main drive

Diesel engine	Mercedes-Benz OM 460
	LA Euromot 3B
Electric motor	-
Power (in kW/PS)	375 / 510

Carriage

Top speed (in km/h)	80
---------------------	----

Weight

Weight basic model (in kg)	20500
Permitted axle load (in kg)	18000
Permitted support load (in kg)	10000
Permitted total weight (in kg)	28000

Measurements transport position

Length (in mm)	11960
Width (in mm)	2550
Height (in mm)	3990

Control system

JES	
VARIO-Flex	✓
IBC	✓
DIP	✓
Sensotronic	✓
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
15-channel remote control	✓
IPS	✓



Application

Ideal machine for changing applications
 Kcomposting (grass cutting, bio-waste)
 trunk wood, roots, scrap wood
 substrate regrinding in biogas plants

Specifics

Varioflex control for economic operation
 variable applications by Twin-Gear drive for optimal rotor speed
 Easy system for simple tool change by just one person
 IPS Impact protection system
 transport with all semi-trailer tractors

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
 D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
 E-Mail: info@jenz.de